



## U20-T

### Lightweight Abrasion Resistance U20-T

Lightweight with good flexibility and compressibility, U20 has nearly all the abrasion and environmental resistance as our U30. Ideal for Oil Mist applications. U20 is constructed of 20-MIL thick urethane. Recommended for Vertical Panel Saw, and Edge Bander.

Abrasion Resistant

Fume Removal

Moisture Resistant

UV/Ozone Resistant



#### Specifications

**Construction:** 20-MIL polyether polyurethane reinforced with a spring steel wire helix.

**Color:** Translucent

**Standard Lengths:** 10 ft. & 25 ft.

**Temp. Range:** -65°F to 200°F

Diameter	Part #	Working Pressure (PSI)	Vacuum (inHg)	CL Bend Radius (in.)	Compression Ratio	Wall Thickness (in.)	Weight (lbs/ft.)
2"	02U20-T	25	>29	2.0	1 ft / 3 in	.020	.17
3"	03U20-T	25	29	2.5	1 ft / 3 in	.020	.30
4"	04U20-T	18	22	3.0	1 ft / 3 in	.020	.39
5"	05U20-T	16	17	3.5	1 ft / 3 in	.020	.48
6"	06U20-T	13	13	4.0	1 ft / 3 in	.020	.66
7"	07U20-T	13	11	5.0	1 ft / 3 in	.020	.77
8"	08U20-T	11	11	5.5	1 ft / 3 in	.020	.86
9"	09U20-T	10	10	6.0	1 ft / 3 in	.020	.97
10"	10U20-T	7	5	6.5	1 ft / 3 in	.020	1.07
12"	12U20-T	7	3	8.0	1 ft / 3 in	.020	1.29

Pressure and Vacuum data based on straight lengths of hose at ambient temp. 72° F.

Due to market changes and fluctuations beyond our control, specifications and pricing subject to change without notice. Buyers subject to terms and conditions of sale. Many states and localities have codes and regulations governing sales, construction, installation and or use of Products for certain purposes, which may vary from those in neighboring areas. While Air Handling Systems by Manufacturers Service Co., Inc. attempts to assure that its Products comply with such codes, it cannot guarantee compliance, and cannot be responsible for how the Product is installed or used. Before purchase and use of a Product, please review the Product application, national & local codes, regulations, and be sure that the Product, installation, and use will be in compliance. Copyright Air Handling Systems.