



AH2P

Flame Retardant Polyester Neoprene AH2P

AH2P is strong, flexible and flame retardant to UL94V-0 rating, it is suitable for a wide range of applications from welding exhaust to dust collection on conveyors, grinders, buffers, polishers, machine tools, surface grinders, woodworking machines, and removal of smoke, fumes and airborne particles.



Construction: 2-ply 100% polyester neoprene coated flame retardant to UL94V-0 rating with a crush resistant spring steel wire helix

Color: Black

Standard Length: 25 ft. or 12 ft. 6 in. for \$10 cutting charge.

Temp. Range: -40°F to 250°F

Diameter	Part #	Working Pressure (PSI)	Vacuum (inHg)	CL Bend Radius (in.)	Compression Ratio	Wall Thickness (in.)	Weight (lbs/ft.)
2"	02AH2P	33	28	1.8	1 ft/4.8 in	.025	.33
3"	03AH2P	23	27	2.7	1 ft/4.8 in	.025	.50
4"	04AH2P	18	25	3.4	1 ft/6.6 in	.025	.70
5"	05AH2P	14	18	3.9	1 ft/6.6 in	.025	.82
6"	06AH2P	14	14	4.5	1 ft/7.2 in	.025	.94
8"	08AH2P	11	10	5.5	1 ft/7.2 in	.025	1.37
10"	10AH2P	10	5	6.8	1 ft/8.4 in	.025	1.48

Pressure & Vacuum data based on straight lengths of hose at ambient temperature 72°F

Due to market changes and fluctuations beyond our control, specifications and pricing subject to change without notice. Buyers subject to terms and conditions of sale. Many states and localities have codes and regulations governing sales, construction, installation and or use of Products for certain purposes, which may vary from those in neighboring areas. While Air Handling Systems by Manufacturers Service Co., Inc. attempts to assure that its Products comply with such codes, it cannot guarantee compliance, and cannot be responsible for how the Product is installed or used. Before purchase and use of a Product, please review the Product application, national & local codes, regulations, and be sure that the Product, installation, and use will be in compliance. Copyright Air Handling Systems.