



Hangers - Cost-effective Solution

DYNA-TITE CABLE LOCK is the fastest way to secure spiral pipe and equipment, reducing installation labor. A fast, strong, lightweight solution.

The anti-corrosion housing has a stainless steel spring that holds the serrated teeth locking wedges against the 3/16" galvanized wire rope. There is a release pin for easy adjustment.

The working weight load limit per 3/16" wire rope and Cable Lock is 640 lbs. with a 5 to 1 safety factor before breaking. These specifications apply only to Duro-Dyne Cable.



Part No.	Description
30350	Cable Lock package of 10
30206	250 ft Spool of 3/16" dia. wire rope
894075	Cable Cutter

Note: Sold only in packages or full spools

Due to market changes and fluctuations beyond our control, specifications and pricing subject to change without notice. Buyers subject to terms and conditions of sale. Many states and localities have codes and regulations governing sales, construction, installation and or use of Products for certain purposes, which may vary from those in neighboring areas. While Air Handling Systems by Manufacturers Service Co., Inc. attempts to assure that its Products comply with such codes, it cannot guarantee compliance, and cannot be responsible for how the Product is installed or used. Before purchase and use of a Product, please review the Product application, national & local codes, regulations, and be sure that the Product, installation, and use will be in compliance. Copyright Air Handling Systems.