

Spiral Pipe (Single Wall)

Dia.	26 Gauge	24 Gauge	22 Gauge	20 Gauge	18 Gauge
3"	0.8	1.1	1.3	1.5	
4"	1.1	1.4	1.7	2.0	
5''	1.4	1.7	2.1	2.5	3.2
6''	1.6	2.0	2.5	3.0	3.9
7"	1.9	2.4	2.9	3.4	4.6
8"	2.1	2.8	3.3	3.9	5.2
9"	2.4	3.1	3.8	4.4	5.9
10"	2.6	3.4	4.2	4.9	6.5
11"	2.9	3.8	4.6	5.4	7.1
12"	3.2	4.1	5.0	5.9	7.8
13"		4.5	5.4	6.4	8.5
14"		4.8	5.8	6.9	9.1
15"		5.1	6.2	7.4	9.8
16"		5.5	6.6	7.8	10.4
18"		6.1	7.5	8.8	11.7
20"		6.8	8.3	9.8	13.0
22"		7.5	9.1	10.8	14.3
24"		8.2	9.9	11.7	15.6
26"			10.8	12.7	16.9
28"			11.6	13.7	18.2
30"			12.4	14.6	19.5
32"			13.3	15.6	20.8
34"			14.1	16.6	22.0
36"			14.9	17.6	23.3
38"				18.5	24.6
40"				19.5	25.9
42"				20.5	27.2

Weights based on Galvanized steel shown in Lb. Per Foot, also available in Stainless steel, contact us for more information.

Spiral pipe is formed from a coil of metal into a rigid steel tube with a 4-ply spiral lockseam. It has smooth interior for low friction loss with the grooved seam entirely on the outside. This pipe has a resistance to crushing approximately 2 1/2 times that of longitudinal lockseam or welded pipe. Pipe sections can be joined together by Small End Couplings, Easy Connect Collars, or Angle Rings.

Please note that due to market conditions beyond our control, both product specifications and pricing are subject to change without prior notice. All buyers are required to adhere to the terms and conditions of sale. It is important to be aware that different states and localities have their own unique codes and regulations governing the sale, construction, installation, and utilization of products for specific purposes. These regulations may vary from one region to another. Air Handling Systems by Manufacturers Service Co., Inc. cannot guarantee compliance, nor can we assume responsibility for the installation or usage of our products. We strongly urge you to thoroughly review the product's intended application, as well as both national and local codes and regulations, prior to purchase. Copyright © Air Handling Systems.