



AHPU60

Full Vacuum AHPU60

AHPU60 flexible hose is perfect for those applications that require flexibility, and full vacuum rating (2 , 2.5 & 3). Smooth interior design allows for superior flow and maximum efficiency. This flexible hose is commonly used for those applications that require a full vacuum such as CNC suction hold down tables.



Specifications

Construction: 55-MIL heavy weight thermoplastic poly-ether polyurethane with a rigid external ABS helix.

Color: Clear/Blue

Standard Length: 25 ft.

Temp. Range: -40°F to 200°F

Vacuum Rating: Full – equivalent to 28 in/HG (2"-3").

Diameter	Part #	Working Pressure (PSI)	Vacuum (inHg)	CL Bend Radius (in.)	Compression Ratio	Wall Thickness (in.)	Weight (lbs/ft.)
2"	02AHPU60	40	28	4.5	N/A	.055	.5
2.5"	025AHPU60	40	28	5	N/A	.055	.6
3"	03AHPU60	40	28	5.8	N/A	.055	.8

Pressure and Vacuum data based on straight lengths of hose at ambient temp. 72° F.

Due to market changes and fluctuations beyond our control, specifications and pricing subject to change without notice. Buyers subject to terms and conditions of sale. Many states and localities have codes and regulations governing sales, construction, installation and or use of Products for certain purposes, which may vary from those in neighboring areas. While Air Handling Systems by Manufacturers Service Co., Inc. attempts to assure that its Products comply with such codes, it cannot guarantee compliance, and cannot be responsible for how the Product is installed or used. Before purchase and use of a Product, please review the Product application, national & local codes, regulations, and be sure that the Product, installation, and use will be in compliance. Copyright Air Handling Systems.