

U30-AP

Smooth Bore U30-AP

U30-AP Smooth Bore is a clear all thermoplastic polyurethane flex hose with safety yellow reinforced ABS helix. U30-AP has a smooth interior and is lightweight and highly flexible. Clarity of hose allows easy visual check for blockages. External ABS (non metal) helix provides added durability in applications where hose is being dragged.



Specifications

Construction: 30-MIL clear all thermoplastic polyurethane with reinforced ABS (non-metal) helix.

Color: Clear with safety yellow ABS helix.

Standard Length: 25 ft.

Temp. Range: -40°F to 200°F

Diameter	Part #	Working Pressure (PSI)	Vacuum (inHg)	Bend Radius (in.)	Compression Ratio	Weight (lbs/ft.)
2"	02U30-AP	22	29	3.0"	2:1	0.44
3"	03U30-AP	20	29	3.5"	2:1	0.47
4"	04U30-AP	18	26	4.0"	2:1	0.56
6"	06U30-AP	16	16	5.5"	2:1	0.84
8"	08U30-AP	16	6	7.0"	2:1	1.12

Data is provided as a general guide only.

Due to market changes and fluctuations beyond our control, specifications and pricing subject to change without notice. Buyers subject to terms and conditions of sale. Many states and localities have codes and regulations governing sales, construction, installation and or use of Products for certain purposes, which may vary from those in neighboring areas. While Air Handling Systems by Manufacturers Service Co., Inc. attempts to assure that its Products comply with such codes, it cannot guarantee compliance, and cannot be responsible for how the Product is installed or used. Before purchase and use of a Product, please review the Product application, national & local codes, regulations, and be sure that the Product, installation, and use will be in compliance. Copyright Air Handling Systems.