

ULW-T Flexible Hose

Lightweight Abrasion Resistance

Lightweight, transparent, with excellent flexibility and compressibility, ULW-T (formerly U20-T) flexible hose has nearly all the abrasion and environmental resistance that our UMW and UHW have. ULW is constructed of thermoplastic polyure-thane reinforced with a wire helix. Ideal for oil mist applications or dust collection.

Abrasion Resistant Fume Removal Moisture Resistant UV/Ozone Resistant



Specifications

Construction: Polyether polyurethane reinforced

with a spring steel wire helix.

Color: Translucent

Standard Lengths: 10 ft. & 25 ft. Temp. Range: -65°F to 200°F

Diameter	Part#	Working Pressure (PSI)	Vacuum (inHg)	CL Bend Radius (in.)	Compression Ratio	Wall Thickness (in.)	Weight (lbs/ft.)
3"	03ULW-T	25	29	2.5	1 ft / 3 in	.020	.30
4"	04ULW-T	18	22	3.0	1 ft / 3 in	.020	.39
5"	05ULW-T	16	17	3.5	1 ft / 3 in	.020	.48
6"	06ULW-T	13	13	4.0	1 ft / 3 in	.020	.66
8"	08ULW-T	11	11	5.5	1 ft / 3 in	.020	.86

Pressure and Vacuum data based on straight lengths of hose at ambient temp. 72° F.

Please note that due to market conditions beyond our control, both product specifications and pricing are subject to change without prior notice. All buyers are required to adhere to the terms and conditions of sale. It is important to be aware that different states and localities have their own unique codes and regulations governing the sale, construction, installation, and utilization of products for specific purposes. These regulations may vary from one region to another. Air Handling Systems by Manufacturers Service Co., Inc. cannot guarantee compliance, nor can we assume responsibility for the installation or usage of our products. We strongly urge you to thoroughly review the product's intended application, as well as both national and local codes and regulations, prior to purchase. Copyright © Air Handling Systems.