

CVD-B

Chemical Resistance Polyvinyl Chloride

CVD-B is an economical flexible hose with good chemical resistance for **FUMES.** Excellent choice for Applications involving fume removal and satisfying many industrial chemical requirements.



Specifications

Constructed of: Polyvinylchloride

Reinforced with a wire helix

Color: Blue or Clear

Lengths: 25 ft.,12.5 ft. w/ cut charge **Temperature Range:** -20°F to 180°F

Diameter	Part#	Working Pressure (PSI)	Vacuum (inHg)	CL Bend Radius (in.)	Compression Ratio	Wall Thick- ness (in.)	Weight (lbs/ft.)
3"	03CVD-B	24	22	4.25	1 ft / 6 in.	.03	.38
4"	04CVD-B	11	17	5.5	1 ft / 5 in.	.03	.68
5"	05CVD-B	10	14	6.75	1 ft / 5 in.	.03	.81
6"	06CVD-B	8	10	7.5	1 ft / 5 in.	.03	1.1
8"	08CVD-B	7	6	10.5	1 ft / 7 in.	.03	1.42
10"	10CVD-B	7	5	11.75	1 ft / 5 in.	.03	1.43

Pressure and Vacuum data based on straight lengths of hose at ambient temp. 68 °F.

Due to market changes and fluctuations beyond our control, specifications and pricing subject to change without notice. Buyers subject to terms and conditions of sale. Many states and localities have codes and regulations governing sales, construction, installation and or use of Products for certain purposes, which may vary from those in neighboring areas. While Air Handling Systems by Manufacturers Service Co., Inc. attempts to assure that its Products comply with such codes, it cannot guarantee compliance, and cannot be responsible for how the Product is installed or used. Before purchase and use of a Product, please review the Product application, national & local codes, regulations, and be sure that the Product, installation, and use will be in compliance. Copyright Air Handling Systems.